



SAMUDRA

SINGLE PHASE | HIGH SPEED

Horizontal Multi Stage Pressure Boosting System

▶ SPBS



Parameters		Range
Power Rating	(HP)	0.5 - 1.5
Head Range	(m)	20 - 52
Discharge Range	(lpm)	120 - 15
Pipe Size	(mm)	25 x 25
Voltage	(Volts)	230
Speed	(rpm)	2850

Salient Features

- FG 260 grade castings with CED coated
- Hydraulic components material is made of high corrosion resistant stainless steel
- Energy efficient hydraulic & electric design
- TEFC, AC induction motor with "F" class winding for continues operations
- Rigid construction for noiseless operation & vibration free running
- Easy to installation & Compact design
- High quality branded pressure switch, Pressure tank & 5 - Way connector ensures operating at wide demand range & thus increase product life

Application

- Pressure boosting system for house hold requirements for Bathrooms, Kitchen, Residential apartments, Small hotels & commercial complex
- Pressurized water supply to Gardens, Sprayers, Sprinklers, Farm irrigation & water wash applications.



*As the design and manufacture of Samudra pumps are subject to continuous improvement, the product supplied may differ in some details from the specification given.

SAMUDRA PUMPS (INDIA) PVT LTD

Registered Office : Office Block 1, Ground Floor, Senthil Towers, 1078 Avinashi Road, Coimbatore - 641 018, TN, India | Tel. +91 422 498 22 55

Email: info@samudrapumps.com | www.samudrapumps.com | CIN : U31909TZ2020FTC033500